



ARTIC.

600

High storage capacity

The Artic 600 model stands out for its extraordinary storage capacity, of up to 600 cans and 324 0.25-0.5L bottles. Additionally, it has an innovative sale system that avoids product loss of shape and delivery jams. Stands out for its efficient energy consumption.

FEATURES

- Cooling unit with adjustable temperature control.
- Capacity: 600 cans, 324 0.5L bottles (60 cans per channel and 54 0.5L bottles in combined configurations for both formats).
- FIFO (First In First Out) System. Continues renewal with the freshest product. Product dispensing according to loading order.
- LED lighting system with on/off programming.
- 1,699 x 753.5 mm back-lit front advertisement panel.
- Continuous performance self-testing.
- Power mains: 230 V, 50Hz.
- Estimated energy consumption: 650 watts.

STRUCTURE

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with three anchor points.
- High-capacity cash box with lock and optional anti-locking during extraction.
- Injected foam insulation system to guarantee efficient cooling and lower energy consumption.

CREDIT MANAGEMENT

- MDB or Executive protocol.
- Innovative Jofemar coin mechanism with five return tubes for up to five different coin values and the most reliable fraud-prevention systems.
- Allows installation of card and banknote readers.

PROGRAMMING

- General on site programming through the machine's keyboard and a display system for the accounting data, accessible from inside the machine.
- Compatible with the Jofemar EasyFlash handheld terminal for stock control and accounting.
- Compatible with the latest telemetry systems for the end-to-end remote machine management.
- RS232 port with accounting data output.

OPTIONS

- Jofemar banknote reader.
- Jofemar J130 card/key reader or any card reader that uses the MDB protocol.
- Vandal-proof coin entry.
- Modem installation and J-Suite communication interface.



	ARTIC 600
Type of product	0.25-0.5L bottles and cans
Capacity	600 cans
Selections	8
Back-lit front advertisement panel	1,699 x 753.5 mm
Number of channels	Up to 10
Size	1,830 x 1,000 x 856 mm
Weight	409 kg
Energy supply	230 V, 50Hz*
Cooling unit	CFC-free R-134a
Vending protocols	MDB or Executive

*Check for other voltages.



VANDAL-PROOF LOCK



OPTIMISED CAPACITY AND VOLUME



BANKNOTE AND COIN MECHANISM PAYMENT SYSTEMS



SOLID METALLIC STRUCTURE



FIFO SYSTEM



Ctra. Marcilla km 2
31350 PERALTA. Navarra SPAIN
Tel. +34 948 75 12 12
Fax +34 948 75 04 20

www.jofemarvending.com

