

VISION

PAGO
PAYMENT ES PLUS



The payment pod is the perfect solution to completely control satellite vending machines. Side detached master module to control up to a combination of 4 slave vendors type Vision E-S and/or Vision E-S Plus. This new type of multiproduct sale point installation uses up less space and offers a higher variety of products.



VANDAL-PROOF LOCK



BANKNOTE AND COIN MECHANISM PAYMENT SYSTEMS



HEALTH TIMER: EXPIRATION PROGRAMMING BY TEMPERATURE



FEATURES

- Vending machine temperature control through the module.
- Continuous performance self-testing.
- Health timer to prevent selling out-of-date products. Programmable expiration date by selection or channel.
- Adjustable motor torque for each selection.
- Power mains: 230 V, 50 Hz.

COMPATIBILITY

- Satellite Vision E-S and Vision E-S Plus vendors.

STRUCTURE

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with six anchor points.
- High-capacity cash box with lock.

CREDIT MANAGEMENT

- MDB or Executive protocol.
- Innovative Jofemar coin mechanism with five return tubes for up to five different coin values and the most reliable fraud-prevention systems.
- Allows installation of card and banknote readers.

PROGRAMMING

- General on site programming with the machine's keyboard and the LCD screen messages.
- Compatible with the Jofemar EasyFlash tooling for stock control and accounting hand terminal.
- Compatible with the latest telemetry systems for the end-to-end remote machine management.
- RS232 port with accounting data output.
- Telemetry by GSM or GPRS modem using the Jofemar J-SUITE software. Includes data accounting, sales, incidences, prices, programming options or SMS to mobile phones in case of sold out products.

OPTIONS

- Jofemar banknote reader.
- Jofemar J130 card/key reader or any card reader that uses the MDB protocol.
- Control of up to four tubes to return manual loading excess.
- Vandal-proof coin entry.
- Modem installation and J-SUITE communication interface.
- Online operation with real-time control of users and sales.
- Up to four slave vending machine modules for higher capacity and number of selections.
- Receipt printer.
- 10.1" advertisement screen or product selection touchscreen.

	PAYMENT MODULE + E-S PLUS
Temperature	—
Number of trays	8 (in machine)
Number of motors	10 (in machine)
Elevator	Optional (in machine)
Size (mm)	1,830 x 1.051 x 935*
Weight	436 Kg
Energy supply	230 V, 50 Hz**
Cooling unit	Optional (in machine)

*970 mm in Snack Plus and EasyCombo, including payment system module.

**Check for other voltages.

